



liveclose312

High sound pressure three-way passive full frequency speaker

Description

liveclose312 is a subwoofer designed specifically for users who pursue high-quality sound output. The box body is made of baked paint wood material, which not only ensures the beauty of the speaker, but also has good acoustic performance. liveclose312, with its outstanding performance, high-quality materials, and exquisite design, can bring users an excellent sound experience in both professional audio fields and daily entertainment scenarios.

Features

- The combination of 14 inch low-frequency provides high fidelity sound effects.
- The rated power is 1200W, and the maximum can reach 4800W, meeting the needs of various scenarios.
- 15mm laminated board box with iron mesh, sturdy and durable.
- Equipped with NL4 connectors and lifting kits, it can flexibly adapt to various scenarios.
- Reasonable price, excellent performance, and value for money.





liveclose312

High sound pressure three-way passive full frequency speaker

Technical specifications

Frequency Response(-3db)	LF: 110Hz-1.1 kHz (-3dB) MF: 360Hz-4.1 kHz (-3dB) HF: 2kHz-17.5kHz (-3dB)
Frequency Response(-10db)	34Hz-150Hz
Rated Power(AES)	LF: 360W MF: 140W HF: 40W
Max SPL @ 1m	LF: 122dB/128dB (peak) MF: 121 dB/127dB (peak) HF: 118dB/124dB (peak)
Dispersion (H x V)	90 °x 40 °
Sensitivity 1W @ 1m	LF:100dB MF:103dB HF:105dB
Nominal Impedance (Ohm)	8 Ω
Crossover Frequencies	MF/LF: 500Hz, MF/HF:2.5KHz

Physical specifications

Box	14 inch subwoofer
Woofers	1 x 12 inch
Mid driver	1 x 6 inch
Compression driver	44mm high frequency compression driver
Cabinet/Case Material	18mm laminated board
Box surface treatment	Water based coal grey sand surface paint
Grille	Electrostatic powder coating black fine sand matte, 1.2mm low carbon steel
Connector	2 x NL4
Optional Accessories	Lifting kit
Dimensions(W x D x H)	466 × 480 × 708mm
Package Dimensions(W x D x H):	595 × 565 × 825mm
Net weight	35.7kg
Gross weight	39.7kg